

DATA SHEET

ITEM NO. 10012217

Santon Load Disconnecter "Fireman's Switch"

Santon-1000-2x2R-2xT50-BC-PES




Scherries 2 | 84329 Wurmanssquick
info@enwitec.eu

All values in [mm]
Dimensions "blue"
Fastening points "orange"

Internal arrangement and components may differ depending on the variant!

Minimum distances

above	200
below	200
lateral	100
front	800



SCOPE OF DELIVERY

Quantity	Designation
1	Santon Load disconnecter "Fireman's switch"
1	General installation instructions PV-RSS
1	Installation instructions GAK-Standard
1	Quick guide to commissioning the EWS
1	enwitec EWS concept with Santon
1	Circuit diagram
1	Schematic UPS board

Quantity	Designation
1 set	Wall mounting brackets
20	M16 cable gland incl. locknut
3	M20 cable gland incl. lock nut
2	Reduction M20/M16
9	Diaphragm insert EMT 16
2	Diaphragm insertion EMT 20

Status: (a)

The text and illustrations correspond to the technical status at the time of printing and are subject to change without notice. Despite careful editing, all information is provided without guarantee. Liability is excluded.

DATA SHEET

ITEM NO. 10012217

Santon Load Disconnecter "Fireman's Switch"

Santon-1000-2x2R-2xT50-BC-PES

TECHNICAL DATA

NOMINAL VALUES		• applicable / - not applicable
Rated insulation voltage U_i	[VDC]	1000
Rated operating voltage U_e	[VDC]	1000
Rated current I_{nA} (ΣI_{SCSTC})	[ACD]	64
Rated current I_{nA}^* ($=\Sigma I_{SCSTC} \times 1.25$)	[ACD]	80
Number of independent MPP inputs		2
Max. Number of PV strings IN/OUT		4/4
Parallel connected inputs/outputs		2

PRO STRANG		
Rated current I_{nc} ($=I_{SCSTC}$)	[ADC]	16
Design current I_{SCMAX} ($=I_{SCSTC} \times 1.25$)	[ADC]	20

SURGE PROTECTION DEVICE		
Test class according to EN 61643-11 (type)		I+II
Highest permissible continuous voltage U_{cpv}	[VDC]	1000
For type 1: Lightning impulse current max. I_{imp} 10/350	[nA]	5

SWITCH-DISCONNECTOR		
Thermal current I_{th} at 60°C	[A]	50/MPP
Utilisation category according to DIN EN 60947-3		DC-21B
Manufacturer and type designation		Santon XC100.50..Q3A/4pole with undervoltage release 230 VAC and automatic Restart function after power failure

* the design current I_{SCMAX} according to VDE 0100-712:2016-10 includes the factor 1.25 for ISC STC of the PV module or PV string.

Status: (a)

The text and illustrations correspond to the technical status at the time of printing and are subject to change without notice. Despite careful editing, all information is provided without guarantee. Liability is excluded.

DATA SHEET

ITEM NO. 10012217

Santon Load Disconnecter "Fireman's Switch"

Santon-1000-2x2R-2xT50-BC-PES

TECHNICAL DATA

INPUT (TO THE PV GENERATOR)		• applicable / - not applicable
Cable entries		
Fittings (EN 62444)		M16
Clamping range (from - to)	[Ømm]	8 x 5 - 10
Connections		
Connection type		Spring clamp
Stripping length	[mm]	13 - 15
Tightening torque	[Nm]	-
Conductor cross-section (from - to)		
Fine copper wire with ferrule	[mm ²]	2,5 - 6
Fine-stranded copper	[mm ²]	0,5 - 10
Cu-stranded	[mm ²]	0,5 - 10

OUTPUT (TO THE PV INVERTER)		
Cable entries		
Fittings (EN 62444)		M16
Clamping range (from - to)	[Ømm]	8 x 5 - 10
Connections		
Connection type		Spring clamp
Stripping length	[mm]	13 - 15
Tightening torque	[Nm]	-
Conductor cross-section (from - to)		
Fine copper wire with ferrule	[mm ²]	2,5 - 6
Fine-stranded copper	[mm ²]	0,5 - 10
Cu-stranded	[mm ²]	0,5 - 10

Status: (a)

The text and illustrations correspond to the technical status at the time of printing and are subject to change without notice. Despite careful editing, all information is provided without guarantee. Liability is excluded.

DATA SHEET

ITEM NO. 10012217

Santon Load Disconnecter "Fireman's Switch"

Santon-1000-2x2R-2xT50-BC-PES

TECHNICAL DATA

EARTH CONNECTION		• applicable / - not applicable
Cable entries		
Fittings (EN 62444)		M20
Clamping range (from - to)	[Ømm]	7 - 13
Connections		
Connection type		Screw terminal
Stripping length	[mm]	19
Tightening torque	[Nm]	2,5
Conductor cross-section (from - to)		
Fine copper wire with ferrule	[mm²]	1,5 - 16
Fine-stranded copper	[mm²]	-
Solid or stranded copper wire	[mm²]	2,5 - 25

COMMUNICATION AND MONITORING		
Interface available		•
Interface type		Undervoltage release and feedback loop
Cable entries		
Fittings (EN 62444)		M16/M20
Clamping range (from - to)	[Ømm]	2 X 4,5 - 10 2 X 4,5 - 13
Connections		
Connection type		Spring clamp
Stripping length	[mm]	10 - 12
Tightening torque	[Nm]	-
Conductor cross-section (from - to)		
Fine copper wire with ferrule	[mm²]	1 - 2,5
Fine-stranded copper	[mm²]	0,25 - 4
Cu-stranded	[mm²]	0,25 - 4

Status: (a)

The text and illustrations correspond to the technical status at the time of printing and are subject to change without notice. Despite careful editing, all information is provided without guarantee. Liability is excluded.

DATA SHEET

ITEM NO. 10012217

Santon Load Disconnecter "Fireman's Switch"

Santon-1000-2x2R-2xT50-BC-PES

TECHNICAL DATA

GENERAL		• applicable / - not applicable
Dimensions WxHxD (without screw connections)	[mm]	300 x 400 x 200
Weight, approx.	[kg]	6,5
Operating temperature range	[°C]	-20...+40
Temperature - transport/storage (24 hours 70°C)	[°C]	-20...+50
Humidity - condensing permitted		-
Humidity - permissible range	[%]	5...95
max. installation height above N.N.	[m]	2000
Protection class IP (EN 60529) _{ta} = 40°C		65
Outdoor suitability (protected area)		-
Protection class (EN 61140)		II
Housing material		Polyester
RoHS-compliant (2011/65/EU)		-
Housing colour		similar to RAL 7035
Lid		Hinged door
Mounting type		Wall mounting
Closure type		Double-bit closure
OTHER		
Customs tariff number		85371098

Status: (a)

The text and illustrations correspond to the technical status at the time of printing and are subject to change without notice. Despite careful editing, all information is provided without guarantee. Liability is excluded.